

# INTRODUCING RAZOR *GEN2* (LEVEL II AND IIIA)

## INNOVATIVE FEATURES

- Razor-thin construction
- Hybrid build for extended wearability
- Reinforced stopping power


*Detailed specifications available upon request*

## COMMON SPECIAL THREATS


*\*Armor tested to varying rounds - see preceding pages for exact threats tested*

II

IIIA




5.7 x 28, 40 gr. FNH  
SS197SR



5.7 x 28, 40 gr. FNH  
SS197SR




9mm, 124 gr. Luger +P  
GDHP



5.7 x 28, 27 gr. FNH  
SS195LF



.357 SIG, 125 gr. Gold  
Dot HP



9mm, 124 gr. Luger +P  
GDHP



.44 Rem. Magnum,  
240 gr. Hydra-Shok



12 Gauge, 1 oz. Rifled  
Slug



Certified to NIJ-0101.06 ballistic requirements

**Ultimate concealability** - Our thinnest ballistic offering gives officers incredible protection in an extremely light weight solution.

**Top tier protection** - The Razor armor has been built to match the most strenuous requirements, including the NIJ 0101.06 certification. The level II and IIIA models are capable of stopping some of the most advanced rounds available.

WEAR FACE - THIS SIDE TO BE WORN AGAINST BODY

**RAZOR™**  
BALLISTIC SYSTEM

MODEL: \_\_\_\_\_  
 LAST NAME: \_\_\_\_\_  
 FIRST NAME: \_\_\_\_\_  
 SIZE: \_\_\_\_\_  
 SERIAL #: \_\_\_\_\_  
 LOT #: \_\_\_\_\_  
 LOCATION OF MANUFACTURE: CENTRAL LAKE, MI 49822  
 DATE OF MANUFACTURE: \_\_\_\_\_  
 DATE OF ISSUE: \_\_\_\_\_  
 MANUFACTURER'S DECLARED WARRANTY PERIOD: 5 YEARS  
 SALES ORDER NUMBER: \_\_\_\_\_  
 THREAT LEVEL: NIJ-0101.06

This model of armor has been determined to comply with NIJ Standard 0101.06 by the NIJ Compliance Testing Program and is listed on the NIJ Compliant Protective List.

**WARNING!**  
This garment is rated ONLY for the ballistic threat level stated above. It is NOT intended to protect against rifle fire or sharp-edged or pointed instruments.

**BALLISTIC PAD CARE INSTRUCTIONS**  
 1. Wipe with damp cloth.  
 2. DO NOT MACHINE WASH or MACHINE DRY.  
 3. DO NOT BLEACH, DRY CLEAN or IRON.

**ARMOR EXPRESS™**  
ARMOREXPRESS.COM

788 N. W. 88 - PO BOX 516 - CENTRAL LAKE, MI 49822

WEAR FACE - THIS SIDE TO BE WORN AGAINST BODY

# RAZOR<sup>GEN2</sup>

# LEVEL II

## TECHNICAL SPECIFICATIONS

<b>Model Designation</b>	RZRG2-A-II
<b>Certified to NIJ-0101.06 Threat Level</b>	II
<b>Test ID #</b>	AEX09-001929
<b>NIJ Certified Sizes</b>	C1 - C5
<b>Gender</b>	Neutral
<b>Ballistic Material</b>	Twaron® Flex Woven Aramid & Dyneema® UHMWPE
<b>Pad Cover</b>	Seam-sealed, waterproof Ripstop Nylon

<b>Weight (Areal Density)</b>	0.67 lbs/ft <sup>2</sup>
<b>Thickness</b>	0.140 in
<b>V-50 - 9mm</b>	1,822 ft/s
<b>V-50 - .357 Mag.</b>	1,727 ft/s
<b>Certification BFS - 9mm</b>	32.7 mm
<b>Certification BFS - .357 Mag.</b>	35.90 mm
<b>Warranty</b>	5 Years

## SPECIAL THREATS\*

Weapon	Ammunition
S&W M&P 9mm	Winchester 9mm Luger +P+ 127gr. T-SERIES
.44 REM. MAG	Federal Premium 240gr. HYDRA-SHOK
FN HERSTAL 5.7x28	40gr. Hornady V-Max SS197SR SC
S&W M&P .357 SIG	125gr. GDHP 54234

\*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

# RAZOR<sup>GEN2</sup>

# LEVEL IIIA

## TECHNICAL SPECIFICATIONS

<b>Model Designation</b>	RZRG2-A-III A
<b>Certified to NIJ-0101.06 Threat Level</b>	III A
<b>Test ID #</b>	AEX09-002407
<b>NIJ Certified Sizes</b>	C1 - C5
<b>Gender</b>	Neutral
<b>Ballistic Material</b>	Twaron® Flex Woven Aramid & Dyneema® UHMWPE
<b>Pad Cover</b>	Seam-sealed, waterproof Ripstop Nylon

<b>Weight (Areal Density)</b>	0.93 lbs/ft <sup>2</sup>
<b>Thickness</b>	0.21 in
<b>V-50 - .357 SIG</b>	1,908 ft/s
<b>V-50 - .44 Mag.</b>	1,746 ft/s
<b>Certification BFS - .357 SIG</b>	30.2 mm
<b>Certification BFS - .44 Mag.</b>	39.5 mm
<b>Warranty</b>	5 Years

**Passed DEA protocol dated 12-03-2009**

## SPECIAL THREATS\*

Weapon	Ammunition
BROWNING 12ga.	2 3/4" 1 OZ. FED. LE127 RS
FN HERSTAL 5.7x28	27gr. SS195LF
S&W M&P 9mm	Winchester Ranger 9mm +P+ RA9TA
FN HERSTAL 5.7x28	40gr. SS197SR V-MAX

\*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

# RAZOR *GEN2 FEMALE*

# LEVEL II

## TECHNICAL SPECIFICATIONS

<b>Model Designation</b>	RZRG2-A-II-FEM
<b>Certified to NIJ-0101.06 Threat Level</b>	II
<b>Test ID #</b>	AEX09-002590
<b>NIJ Certified Sizes</b>	C1 - C5
<b>Gender</b>	Female
<b>Ballistic Material</b>	Twaron® Flex Woven Aramid & Dyneema® UHMWPE
<b>Pad Cover</b>	Seam-sealed, waterproof Ripstop Nylon

<b>Weight (Areal Density)</b>	0.74 lbs/ft <sup>2</sup>
<b>Thickness</b>	0.18 in
<b>V-50 - 9mm</b>	1,784 ft/s
<b>V-50 - .357 Mag.</b>	1,680 ft/s
<b>Certification BFS - 9mm</b>	29.8 mm
<b>Certification BFS - .357 Mag.</b>	35.4 mm
<b>Warranty</b>	5 Years

## SPECIAL THREATS\*

Weapon	Ammunition
FN HERSTAL 5.7x28	SS197SR 40gr. V-MAX
S&W .44 REM. MAG.	240gr. HYDRA-SHOK P44HS1
S&W M&P 9MM	SPEER LE 124gr. GDHP 53617
S&W M&P .357 SIG	SPEER LE 125gr. GDHP 54234

\*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

# RAZOR<sup>GEN2 FEMALE</sup>

# LEVEL IIIA

## TECHNICAL SPECIFICATIONS

<b>Model Designation</b>	RZRG2-A-III-A-FEM
<b>Certified to NIJ-0101.06 Threat Level</b>	IIIA
<b>Test ID #</b>	AEX09-002456
<b>NIJ Certified Sizes</b>	C1 - C5
<b>Gender</b>	Female
<b>Ballistic Material</b>	Twaron® Flex Woven Aramid & Dyneema® UHMWPE
<b>Pad Cover</b>	Seam-sealed, waterproof Ripstop Nylon

<b>Weight (Areal Density)</b>	0.97 lbs/ft <sup>2</sup>
<b>Thickness</b>	0.23 in
<b>V-50 - .357 SIG</b>	2,020 ft/s
<b>V-50 - .44 Mag.</b>	1,830 ft/s
<b>Certification BFS - .357 SIG</b>	26.8 mm
<b>Certification BFS - .44 Mag.</b>	36.6 mm
<b>Warranty</b>	5 Years

**Passed DEA protocol dated 12-03-2009**

## SPECIAL THREATS\*

Weapon	Ammunition
FN HERSTAL 5.7x28	SS197SR 40gr. V-MAX
FN HERSTAL 5.7x28	SS195LF 27gr.
S&W M&P 9MM	Winchester Ranger 9mm +P+ RA9TA
12ga BROWNING	2.75" 1oz Rifled Slug

\*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.